

STANDARD PILLOWCASE

Three fabrics cut to the following sizes:

Main Fabric: 26" x width of fabric

Trim Fabric: 2" x width of fabric strip (fold in half lengthwise)

Border Fabric: 10 1/2" x width of fabric

Sewing:

1. Place the raw edges of the folded trim fabric along the right side of one of the long edges of the main fabric
2. Lay the border fabric on top of the trim, right sides together. Pin all layers and sew 1/4" seam through all four layers.
3. Press the seam toward the border. Trim the side edges of all fabrics along the sides to even it up.
4. With right sides together, seam the side and bottom edges.
5. Turn under 1/4" along the raw edge of the border and press.
6. Fold the pressed edge of the border inside, press and pin to cover the seam line.
7. Topstitch to secure the border in place. You can stitch on either the border or the trim.
8. Try using a decorative machine stitch and contrasting thread for an additional design element.

For larger sizes, cut the fabrics to the sizes listed and follow the directions above.

QUEEN SIZE PILLOWCASE

Main Fabric: 30" x width of fabric

Trim Fabric: 2" x width of fabric strip (fold in half lengthwise)

Border Fabric: 10 1/2" x width of fabric

KING SIZE PILLOWCASE

Main Fabric: 34" x width of fabric

Trim Fabric: 2" x width of fabric strip (fold in half lengthwise)

Border Fabric: 10 1/2" x width of fabric